

09/936915

JC16 Rec'd PCT/PTO SEP 19 2001

PATENT

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Narumi HIROTA et al.

Serial No.: New Application (PCT/JP01/00518)

Filed: September 19, 2001

For: VIDEO APPLIANCE, HOLDING DEVICE, AND
MANUFACTURING METHOD OF HOLDING DEVICE

PRELIMINARY AMENDMENT

Commissioner for Patents
Washington, D.C. 20231

Sir:

Prior to examination of the above-identified application,
please enter the following specification changes as noted below:

IN THE CLAIMS:

Please amend claims 7, 12 and 14 below:

7. (Amended) The CRT holding device of claim 3, wherein said
rib section has a section shaped like a gutter having a groove.

12. (Amended) The video appliance of claim 10, wherein said rib section has a section shaped like a gutter having a groove.

14. (Amended) The video appliance of claim 8, further comprising a front panel attached to a screen surface side of the CRT.

Please add new claims 25-28 below:

25. (New) The video appliance of claim 11, wherein said rib section has a section shaped like a gutter having a groove.

26. (New) The video appliance of claim 25, further comprising a degaussing coil disposed in the groove of said rib section.

27. (New) The video appliance of claim 10, further comprising a front panel attached to a screen surface side of the CRT.

28. (New) The video appliance of claim 11, further comprising a front panel attached to a screen surface side of the CRT.

REMARKS

Claims 1-24 remain herein. Claims 7, 12 and 14 have been amended and claims 25-28 added.

Examination of this application on its merits is respectfully requested.

Respectfully submitted,

PARKHURST & WENDEL, L.L.P.

September 19, 2001
Date


Roger W. Parkhurst
Registration No. 25,177

Attachment:
Claims Mark Up

RWP/ame

Attorney Docket No. MEIC:111

PARKHURST & WENDEL, L.L.P.
1421 Prince Street, Suite 210
Alexandria, Virginia 22314-2805
Telephone: (703) 739-0220

one of magnesium alloy, aluminum alloy, and zinc alloy.

7. The CRT holding device of claim 3, 4, 5, or 6, wherein said rib section has a section shaped like a gutter having a groove.

5

8. A video appliance comprising a rib section for holding a cathode-ray tube (CRT) from a rear side of the CRT, said rib section having a shape similar to a shape of a funnel of the CRT.

10 9. The video appliance of claim 8, wherein said rib section has ribs extending in a plurality of directions, respectively.

10. A video appliance comprising:
a rib section having a shape similar to a shape of a funnel of a cathode-ray tube (CRT); and
a frame formed unitarily with said rib section, said frame having a shape corresponding to a shape of a panel of the CRT,
wherein said rib section and frame hold the CRT from a rear side of the CRT.

20

11. A video appliance comprising:
a rib section having a shape similar to a shape of a funnel of a cathode-ray tube (CRT);
a frame having a shape corresponding to a shape of a panel of the CRT;
25 and
a support base linked to at least one of said rib section and frame,
wherein the CRT is held in self-standing manner from a rear side of the

SEARCHED
INDEXED
SERIALIZED
FILED

CRT.

12. The video appliance of claim 10 or 11, wherein said rib section has a section shaped like a gutter having a groove.

5

13. The video appliance of claim 12, further comprising a degaussing coil disposed in the groove of said rib section.

14. The video appliance of claim 8, 9, 10, 11, 12, or 13, further comprising a front panel attached to a screen surface side of the CRT.

15. A cathode-ray tube (CRT) holding device comprising:
a rib section for holding a CRT from a rear side of the CRT, said rib section having a shape similar to a shape of a funnel of the CRT; and
15 a runner section for pouring injection material from an injection molding machine, said runner section being provided as a part of said rib section.

16. A cathode-ray tube (CRT) holding device comprising:
a rib section having a shape corresponding to a shape of a funnel of a
20 CRT;
a frame formed unitarily with said rib section, said frame having a shape corresponding to a shape of a panel of the CRT; and
a runner section for pouring injection material from an injection molding machine, said runner section being provided as a part of the rib section.

25

17. A cathode-ray tube (CRT) holding device comprising:
a rib section having a shape corresponding to a shape of a funnel of a